



Adjustable pedestal 150/260 mm

Note: Always calculate the height you want to catch up by deducting the thickness of the coating in order to obtain the necessary pedestal size.

Application & use

Creation of terraces in porcelain stoneware, stone, concrete or gratings for pedestrian use.

Installation is only done on stabilized ground with self-supporting slabs of class T7, T11 or F + and measuring at least 2 cm thick.

Technical Characteristics

Composition : polypropylene (recycled and recyclable)

Color : black and red

Origine : France

Garantee : 10 years

Conformity : norm DTU 43.1

Use : pedestrian only

Base diameter : 200 mm

Head diameter : 120 mm

Lugs dimension : height 15 mm / thickness 3 mm

Resistance to temperatures : from -40°C to +60°C

Resistances to atmospheric agents : UV and freeze

Load resistance : up to 1 ton

Product Advantage

- + Simplified ground preparation
- + Base designed to ensure proper drainage of stormwater
- + Quick and convenient installation without glue or joint
- + Compatible with many slab coatings
- + Adjustment to the millimeter thanks to the nut without additional tools
- + Removable lugs for a smooth head (for edging)
- + **Compatible accessories:** slab plate, lateral supports, vibration buffers, self-leveling disc as well as 60 and 110 mm extensions.