



Adjustable pedestal 8/20 mm

The adjustable slab pedestal from 8 to 20 mm allows the installation of terrace of low height. It can be adjusted from 8 to 15 mm without the wedge or up to 20 mm with. It is ideal for creating a roof top or covering an existing

Application & use

Creation of terraces in porcelain stoneware, stone, concrete or gratings for pedestrian use.

Installation is only done on stabilized ground with self-supporting slabs of class T7, T11 or F + and measuring at least 2 cm thick.

Technical Characteristics

Composition : polypropylene (recycled and recyclable)

Color : black

Origine : France

Garantee : 10 years

Conformity : norm DTU 43.1

Use : pedestrian only

Base diameter : 170 mm

Head diameter : 125 mm

Lugs dimension : height 12 mm / thickness 3 mm

Resistance to temperatures : from -40°C to +60°C

Resistances to atmospheric agents : UV and freeze

Load resistance : up to 1 ton

Product Advantage

- + Simplified ground preparation
- + Base designed to ensure proper drainage of stormwater
- + Quick and convenient installation without glue or joint
- + Compatible with many slab coatings
- + Adjustment to the millimeter thanks to the nut without additional tools
- + Removable lugs for a smooth head (for edging)
- + **Compatible accessory : vibration buffers**