



## Adjustable pedestal 90/150 mm

The paving pedestal is adjustable in height from 90 to 150 mm at millimeter near using the red ring. The head of the paving pedestal is equipped with 4 pins which serve to keep the slabs in their place.

**Note:** Always calculate the height you want to catch up by deducting the thickness of the coating in order to obtain the necessary pedestal size.



Made In France

### Application & use

**Creation of terraces in porcelain stoneware, stone, concrete or gratings for pedestrian use.**

The installation on pedestals requires the use of a covering with a minimum thickness of 2cm. It is possible to use tiles (porcelain stoneware), concrete slabs, reconstituted stone or rectified natural stone (5cm thick).

### Technical Characteristics

**Composition :** polypropylene (recycled and recyclable)

**Color :** black and red

**Origine :** France

**Garantee :** 10 years

**Conformity :** norm DTU 43.1

**Use :** pedestrian only

**Base diameter :** 200 mm

**Head diameter :** 120 mm

**Lugs dimension :** height 15 mm / thickness 3 mm

**Resistance to temperatures :** from -40°C to +60°C

**Resistance to atmospheric agents :** UV and freeze

**Load resistance :** up to 1 ton

### Product Advantages

- + Simplified ground preparation
- + Base designed to ensure proper drainage of stormwater
- + Quick and convenient installation without glue or joint
- + Compatible with many slab coatings
- + Adjustment to the millimeter thanks to the nut without additional tools
- + Removable lugs for a smooth head (for edging)
- + **Compatible accessories: slab plate, lateral supports, vibration buffers and self-leveling disc, YEED ClipSystem, and 60 mm and 110 mm extensions.**

