



Self-leveling pedestal 175/285 mm

The self-levelling pedestal for paving is composed of a disc-shaped base that allows to create or compensate up to 5% of slope on 1 meter. It is ideal for laying on sloping or uneven terrain.

Note: Always calculate the height you want to catch up by deducting the thickness of the coating in order to obtain the necessary pedestal size.



Made In France

Application & Use

Creation of terraces in porcelain tile, stone, concrete or grating for pedestrian use.

The installation on pedestals requires the use of a covering with a minimum thickness of 2cm. It is possible to use tiles (porcelain stoneware), concrete slabs, reconstituted stone or rectified natural stone (5cm thick).

Technical Characteristics

Composition : polypropylene (recycled and recyclable)

Color : black and red

Origine : France

Garantee : 10 years

Conformity : norm DTU 43.1

Use : pedestrian only

Disc diameter : 200 mm

Head diameter : 120 mm

Lugs dimension : height 15 mm / thickness 3 mm

Resistance to temperatures : from -40°C to +60°C

Resistance to atmospheric agents : UV and freeze

Load resistance : up to 1 ton

Product Advantages

- + Simplified ground preparation
- + Base designed to ensure proper drainage of stormwater
- + Quick and convenient installation without glue or joint
- + Compatible with many slab coatings
- + Adjustment to the millimeter thanks to the nut without additional tools
- + Removable lugs for a smooth head (for edging)
- + **Compatible accessories :** vibration buffers, slab plate, lateral supports, YEED Clip System, 60 and 110 mm extensions.

