



Adjustable pedestal 40/60 mm

The paving pedestal is adjustable in height from 40 to 60 mm at millimeter near using the red ring. The head of the paving pedestal is equipped with 4 pins which serve to keep the slabs in their place.

Note: Always calculate the height you want to catch up by deducting the thickness of the coating in order to obtain the necessary pedestal size.



Made In France

Application & use

Creation of terraces in porcelain stoneware, stone, concrete or gratings for pedestrian use.

The installation on pedestals requires the use of a covering with a minimum thickness of 2cm. It is possible to use tiles (porcelain stoneware), concrete slabs, reconstituted stone or rectified natural stone (5cm thick).

Technical Characteristics

Composition : polypropylene (recycled and recyclable)

Color : black and red*

Origine : France

Garantee : 10 years

Conformity : norm DTU 43.1

Use : pedestrian only

Base diameter : 200 mm

Head diameter : 120 mm

Lugs dimension : height 15 mm / thickness 3 mm

Resistance to temperatures : from -40°C to +60°C

Resistance to atmospheric agents : UV and freeze

Load resistance : up to 1 ton

Product Advantages

- + Simplified ground preparation
- + Base designed to ensure proper drainage of stormwater
- + Quick and convenient installation without glue or joint
- + Compatible with many slab coatings
- + Adjustment to the millimeter thanks to the nut without additional tools
- + Removable lugs for a smooth head (for edging)
- + **Compatible accessories: slab plate, lateral supports, vibration buffers and self-leveling disc, YEED ClipSystem**

